

PRODUCT DESCRIPTION

PIGMENTA; is a water based topcoat which can be collered.

FEATURES

- High elasticity
- High resistance to UV Rays
- Natural look after application
- Provides high resistance against external conditions

RECOMMENDED USES

It is used for wooden panels, wooden shutters, wooden doors and windows.

GLOSS OPTIONS

Product Code	Gloss
BW426.20.XXXX	20
BW426.40.XXXX	40

PRODUCT SPECIFICATIONS

Product Type	: Water Based
Viscosity (cps)	: 1500 - 2500
Specific Gravity (kg/lt)	: 1,2 ± 0,02
Weight Solids (%)	: 47 ± 1
pH	: 8,5 - 9,0
Recommended Number of Coats	: 2
Recommended Application (gr/m²)	: 80 - 130
Practical Coverage (m²/lt)	: 8-10
Forced Air Drying (150 g/m² application)	
Flash off	:20 min(30°C)
Oven/Laminar air	:45 min (45°C)
Cooling	:15 min (20°C)
Dry Time (20°C, % 45-65 RH, 100 g/m²)	
Dust free	: 30 min.
Touch dry	: 2 hours
Sanding	: 4 hours
Waiting between coats	: 4 - 6 hours
Stackable	: min 24 hours

COLOR OPTIONS

Color Code	Color Information
1000	BIANCO
1715	IVORY
7235	GREY CHIARO
7243	GREY SCURO
5224	RUSTICO BLU
5212	BLU CIELO
2704	GIALLO
6305	VERDE SCURO
8416	MARRONE
3304	ROSSO

SURFACE PREPARATION

The substrate has to be properly sanded and cleaned up from dust particles.

Wood must be well seasoned (max. 12% humidity). Always clean well the surfaces, removing all traces of grease, waxes and resins. Perform sanding with 180 grit paper for hardwoods.

APPLICATION

Conventional Spray: Recomendado to use 2-2,5 mm nozzle with 3-4 air bar. It can be dilute with 5-10 % water.

Application Equipment

- Spray
- Brush

STORAGE & HANDLING

The shelf life is 12 months if the products are stored in an environment with temperature between 5 - 35°C.

Coating left overs (washing waters, waters from spray booths, used coatings) must be disposed according to local regulations. Never dispose residues directly into drains.

Application tools must be cleaned with water after use. Keep in dry and cool storage area.

HEALTH & SAFETY

Observe the precautionary notices which are displayed on the container.

Good ventilation must be provided in the working environment.

For full Health and Safety information, please refer to Safety Data Sheet.

Gloves and suitable protective equipment must be worn while using these products.

WARNING

The product application on substrate must be done in an environment with no less than 12°C.

Coatings applications at low temperatures may cause lower chemical and mechanical properties than standard performances.

Mix the product before use.

Application equipment should be cleaned with water and product residues should never be given to the sewer.

TRANSPORT INFORMATION

Freight Classification : Paint

Packaging : 0,75 LT ; 2,5 LT ; 20 LT



Apply with brush



Apply with spray



Stir



Store in cool place



Protect from freezing